

This is an Accepted Manuscript of an article published by Taylor & Francis in Journal of Maps on 18 September 2014 (date of online availability) available online:
<http://www.tandfonline.com/10.1080/17445647.2014.957251>

Manual mapping of drumlins in synthetic landscapes to assess operator effectiveness

Hillier¹, J. K., Smith², M. J., Armugam¹, R., Barr³, I., Boston⁴, C., Clark⁵, C. D., Ely⁵, J., Fankl⁶, A., Greenwood⁷, S. L., Gosselin⁸, L., Hättestrand⁹, C., Hogan¹⁰, K., Hughes¹¹, A. L. C., Livingstone⁵, S. J., Lovell³, H., McHenry¹², M., Munoz¹³, Y., Pellicer¹⁴, X. M., Pellitero¹⁵, R., Robb¹⁰, C., Roberson¹⁶, S., Ruther¹⁷, D., Spagnolo¹⁵, M., Standell¹, M., Stokes¹⁸, C. R., Storrar¹⁸, R., Tate¹⁹, N. J., Wooldridge²⁰, K.

¹Department of Geography, Loughborough University, LE11 3TU, UK.

²School of Geography, Geology and Environment, Kingston University, KT1 2EE, UK.

³School of Geography, Archaeology and Palaeoecology, Queen's University Belfast, BT7 1NN, UK

⁴Dept. Geography, University of Portsmouth, Portsmouth, PO1 3HE, UK.

⁵Department of Geography, The University of Sheffield, Sheffield, S10 2TN, UK

⁶Department of Geography, Ghent University, Krijgslaan 281, S8 9000 Ghent, Belgium.

⁷Department of Geological Sciences, Stockholm University, 10691 Stockholm, Sweden.

⁸Departement of Geography, Université du Québec à Rimouski, G5L 3A1, Canada.

⁹Department of Physical Geography and Quaternary Geology, Stockholm University, SE-106 91, Stockholm.

¹⁰British Antarctic Survey, High Cross, Madingley Road, Cambridge, CB3 0ET UK.

¹¹Department of Earth Science, University of Bergen and Bjerknes Centre for Climate Research, Allegaten 41, Bergen 5007, Norway.

¹²School of Environmental Sciences, University of Ulster, Coleraine, BT52 1SA, UK

¹³Department of Earth and Atmospheric Sciences, University of Houston, Houston, Texas, USA.

¹⁴Geological Survey of Ireland, Beggars Bush Buildings, Haddington Road, Dublin 4.

¹⁵Department of Geography & Environment, School of Geosciences, University of Aberdeen, St. Mary's Building, Elphinstone Road, Aberdeen, AB24 3UF.

¹⁶British Geological Survey, Colby House, Stranmillis Court, Belfast ,BT9 5BF

¹⁷SognHøgskulen i Sogn og Fjordane, Postboks 133, 6851 Sogndal.

¹⁸Department of Geography, Durham University, Durham, DH1 3LE, UK

¹⁹Department of Geography, University of Leicester, Leicester, LE1 7RH

²⁰ Department of Geographical & Life Sciences, Canterbury Christ Church University, North Holmes Road, Canterbury, Kent, CT1 1QU.

Abstract

Mapped topographic features are important for understanding processes that sculpt the Earth's surface. This paper presents maps that are the primary product of an exercise that brought together 27 researchers with an interest in landform mapping where the efficacy and causes of variation in mapping were tested using novel synthetic DEMs containing drumlins. The variation between interpreters (e.g., mapping philosophy, experience) and across the study region (e.g., woodland prevalence) opens these factors up to assessment. *A priori* known answers in the synthetics increase the number and strength of conclusions that may be drawn with respect to a traditional comparative study. Initial results suggest that overall detection rates are relatively low (34-40%), but reliability of mapping is higher (72-86%). The maps form a reference dataset.

Keywords: Glacial landform, Synthetic, Drumlin, Mapping, DEM, Objective

1. Introduction

Mapping the location and distribution of topographic features on the Earth's surface has long been considered an important means for developing an understanding of the processes that formed them (e.g., Hollingsworth, 1931; Menard, 1959). Ever since photography has been used to survey, there has been a requirement to identify features within an image. Aerial photography facilitated the holistic visualisation of features within the landscape and made photo interpretation a key tool for academic study. However, it was the military exploitation of aerial imagery that drove early development in its interpretation (e.g., Anonymous, 1963; Colwell, 1960), which was later mirrored in the photogrammetric literature (e.g., Thompson, 1966).

It is against this cultural backdrop of image interpretation that Earth scientists developed qualitative methodologies for mapping landforms; techniques initially used in aerial photography (e.g., Prest et al., 1968) were transferred to satellite imagery (e.g., Punkari, 1980) and then digital elevation models (DEMs; e.g., Evans, 1972; Smith and Clark, 2005). The advent of computers and digital spatial data led to the development of algorithms for the automated identification of landforms (e.g., Behn et al., 2004; Hillier and Watts, 2004; Bue and Stepinski, 2006). Some landforms offer quantitatively distinct boundaries that make their identification relatively simple, for example determining flow paths for river channels using DEMs (e.g., van Asselen and Seijmonsbergen, 2006). However the boundaries of many landforms are poorly defined (e.g., Fisher et al., 2004; Evans, 2012), requiring complex visual and analytical heuristics for landform identification. This has also made automated identification a non-trivial task and it is only in the last decade that significant progress has been made (e.g., Drăguț and Blaschke, 2006; Hillier, 2008; Anders et al, 2011). Even then, anecdotal observation of researchers' preferences and its usage in publications suggests that manual interpretation is generally still considered to be more reliable.

If manual interpretative techniques are preferred for some mapping activities it is important to assess the levels of accuracy and precision that are attainable. However, this is difficult as it is not possible to know *a priori* the actual number of features in a landscape or their 'true' boundaries. It is possible to determine a control, a sub-area within a study, within which interpreters map features that can later be compared with mapping completed for a whole study (e.g., Smith and Clark, 2005). Likewise, it is also possible to compare the mapping of different interpreters to ascertain if there are significant differences between individuals (e.g., Podwysoki et al, 1975; Siegal, 1977). This work suggests that variation in mapping by a single interpreter can be relatively low (Smith and Clark, 2005), but that variation between interpreters can be high. The absolute, as opposed to relative, accuracies however still require investigation.

The purpose of geomorphological mapping is typically to produce quantitative, repeatable, observations of features in the landscape, but to what extent can subjective manual interpretations be reproducible? What is the achievable accuracy of subjective mapping? What is the variation in accuracy and which characteristics of the interpreter and landscape govern any variation? Are there any systematic biases in the mapping, and how do these relate to the definition of the feature's boundary being used in practice? These are important questions to understand when making inferences from data and should guide the development of clear and consistent methodologies for interpretative mapping, yet their investigation is difficult without *a priori* knowledge of landscapes and the variability between both interpreters and the landforms they map. Synthetic DEMs (e.g., Hillier and Smith, 2012), on the other hand, are designed terrains within which key components are known *a priori*, and so they have facilitated some progress on these and related questions. Specifically, synthetic DEMs were used to determine an optimal semi-automated method for drumlin extraction (Hillier and Smith, 2014), and a pilot study on manual mapping (Armugam et al, 2012) tentatively indicated that drumlin amplitude may be the key dimension governing drumlin detectability (Fig. 1c).

This paper and the accompanying maps present the outcomes of an exercise that brought together a variety of researchers with an interest in landform mapping where the efficacy and variation of interpretation between individuals was tested using synthetic DEMs. Initial findings from this work are presented, and the maps form a reference dataset for future work.

2. Methods

2.1 Research Design

In order to test aspects of interpreter mapping, such as 'completeness' (see below), it is necessary to know with certainty exactly which landforms exist in a landscape and where they are, but for incompletely defined landforms in a real landscape this is unknowable.

Thus, a sufficiently realistic DEM containing an *a priori* known answer is required to give these absolute measures of effectiveness (see 'Results'), which traditional mapper inter-comparisons simply cannot provide or estimate. One way to generate this might be to use a 'landscape evolution model' (e.g., Chase, 1992; Braun and Sambridge, 1997) to generate a artificial landscape that is both realistic and statistically comparable to a real landscape including all factors such as vegetation and anthropogenic alteration, but this has not yet been achieved for glacial bedforms. Hillier and Smith (2012) therefore proposed an alternative hybrid method. They used an existing DEM of real terrain and inserted synthetic landforms of known size and shape into it. When generating the synthetic DEM the locations and orientations of the landforms are set. Synthetic DEMs created like this make it possible to assess the ability of interpreters to identify landforms in an absolute sense, something that is not possible with a real landscape. It is possible to produce any number of synthetic variants of a landscape that interpreters can map, and then compare and contrast the output in order to draw conclusions that include quantitative error estimates about absolute accuracy, variability, repeatability, and systematic biases. Thus, subject to establishing the representativeness of the synthetic DEMs used in each case study, this increases the number and strength of conclusions that may be drawn with respect to a traditional comparative study. An experimental approach employing synthetic DEMs is used here; these currently insert only one landform type, however is sufficient to support the aims of the paper and there is no reason why more complex synthetics could not be constructed in the future.

2.2 Choice of landform

For this work drumlins were selected as the landform to be mapped. Drumlins are elongate hills, typically 100s m long and up to a few 10s of metres high (Menzies, 1979; Wellner, 2001; Smith et al., 2007; Clark et al, 2009; Spagnolo et al, 2012; Hillier and Smith, 2014). They are likely formed subglacially, parallel to ice flow (Smith et al, 2007; King et al, 2009; Johnson et al, 2010), and, as they can persist in the landscape, they encode information on the location and direction of flow of former ice cover (e.g., Hollingsworth, 1931; Kleman and

Borgström, 1996; Finlayson et al, 2010) and perhaps even the nature and velocity of ice flow (e.g., Colgan and Mickelson, 1997; Smalley et al, 2000; Stokes and Clark, 2002). Such information is valuable for understanding the histories of past ice sheet change. Thus, they are of scientific interest. Commonly drumlins are mapped manually, often by an individual interpreter (e.g., Hughes, et al, 2010). However, their exact form has not yet been definitively, robustly and quantitatively defined and so a drumlin's spatial footprint is open to interpretation and differs between interpreters (See e.g., Fig 1a Hillier and Smith, 2014). Despite this there has been some limited success in the use of automated algorithms (e.g., Saha et al, 2011). As such, drumlins seem likely to be able to be mapped accurately, reproducibly and objectively, and are regularly interpreted upon this basis, yet making this operational remains a challenge.

2.3 Generation of Synthetic Landscapes

In order to generate synthetic DEMs using the method of Hillier and Smith (2012), a 'donor' DEM is required. This study uses the NextMap DEM of the UK which is an interferometric synthetic aperture radar (IfSAR) product with a spatial resolution of 5 m and vertical accuracy of ~0.5-1 m (Intermap, 2004). Once the DEM is selected it is then necessary to manually identify the drumlins present; Smith et al (2006) mapped the study area using different visualisations of the landscape (i.e., relief shaded in two orthogonal directions, gradient, curvature, local contrast stretch; Fig. 1b). This mapping approach was employed by Smith et al (2006) on multiple occasions in order to both check the repeatability of the mapping and to reduce bias that may have been introduced in any one session. The mapping stage serves two purposes: (1) to parameterise the synthetic drumlins to be inserted in to the DEM, and (2), to allow the removal of the original drumlins.

The population of originally mapped drumlins were parameterised in terms of their shape (i.e., Gaussian) - height (H), width (W), and length (L). These were then used to generate a set of synthetic, idealised, drumlins; each mapped drumlin created one synthetic drumlin,

which retained the same identification number and parameter triplet (H , W , L) wherever it was placed. Visually selected median filters (Hillier and Smith, 2014) were used to quantify H and the morphology, and to remove the original drumlins. The synthetic features were then randomly inserted in a non-overlapping fashion back into the DEM, which also preserved their spatial density and distribution of their orientations. These measures are sufficient to ensure that errors associated with recovery of H , L and W are the same in the synthetics as the original landscape, at least for semi-automated techniques (Hillier and Smith, 2012). This, combined with the use of a real DEM, ensured that the synthetics were statistically representative of the real landscape. Full details of the procedure are outlined in Hillier and Smith (2012). It was intended that drumlin-shaped landforms were equally as difficult to find in the synthetics as they are in reality. The perfect Gaussian shape of the synthetics and their ability to cut across landscape features in an unnatural way may tend to act to make them easier to identify. Conversely, their lack of alignment with each other may make them more difficult to find than natural drumlins. The lack of local parallel alignment was highlighted as a disadvantage during the workshop. As a result five additional DEMs were created where drumlins were aligned perpendicular to the original flow field and avoids confusion with incompletely removed glacial texture in the DEM. If anything, these represent a limiting best case for drumlin detection. The synthetics used do not include parabolic, ovoid or crosscutting drumlins (e.g., Rose and Letzer, 1977; Shaw, 1983; Shaw and Kavill, 1989; Hillier and Smith, 2008; Boyce and Eyles, 1991; MacLachlan and Eyles, 2013), which could complicate mapping.

2.4 Study Area

This work used the same study area as Hillier and Smith (2012) (Fig. 1) which has been mapped in detail by other researchers studying the glacial geomorphology of the region (e.g., Rose and Letzer, 1975, 1977; Smith et al, 2006; Rose and Smith, 2008; Finlayson et al, 2010; Hughes et al., 2010). This area of Scotland sits between the Grampian Highlands to the north and the Southern Uplands to the south and was glaciated during the Last Glacial

Maximum (LGM) and Younger Dryas (YD). It contains two identifiable suites of features interpreted as "classically shaped" (with an elliptical footprint) drumlins (e.g., Chorley, 1959; Reed, 1962). The drumlins mark the presence of flowing ice during these time periods, broadly west to east during the LGM and north to south during the YD, and drumlin dimensions are broadly comparable to those of other drumlins in the UK (Hillier and Smith, 2014). The study area is similar to many previously glaciated regions of the UK in that it contains topographic complexity in the form of regional relief (e.g., hills) and non-glacial anthropogenic 'clutter' (e.g., trees, houses), which vary in their amplitude and spatial density, respectively; it is intended that the variation across the study area in the severity of the challenge posed by aspects of topographic complexity will allow their impacts to be isolated.

2.5 Interpretive Mapping

In order to test the variability of interpretive mapping individual researchers were invited to map the synthetic DEMs using email lists. There were a total of 27 respondents who had a range of experiences and expertise within geomorphology, glaciology, Earth science and remote sensing. They included undergraduate and postgraduate students, faculty and post-doctoral researchers from a range of countries and of different nationalities, although all from Europe or North America with a bias towards the United Kingdom.

In addition, whilst the manuscript and main map present the outputs of this mapping, a workshop was organised in order to present the draft results to participants and drive discussion. The ultimate goal of the project is to highlight the nature of differences between interpreters and begin the development of objective criteria for mapping. In total 25 people completed mapping for the project, with an overlapping set of 24 participants who attended the workshop.

Interpreters were supplied with five raw synthetic DEMs and guidelines clearly stating that each DEM contained exactly 173 drumlins, creating a total dataset of 865 landforms.

Interpreters were requested to prepare the DEMs for mapping using their software of choice and whilst there was an assumption that relief shading, gradient and curvature (Smith and Clark, 2005) may be prominent visualisation techniques, they were not restricted in the use of any particular manipulation. In order to generate a statistically significant number of results interpreters were requested to map:

- drumlin outlines for each DEM using their preferred or 'best' visualisation
- separate sets of outlines individually using each of the relief shaded, gradient and curvature visualisation for two randomly selected DEMs
- mapping of drumlin ridge crests and high points for two randomly selected DEMs using their 'best' method.

Mapping was returned as individual shapefiles and a questionnaire completed, qualitatively surveying individual approaches to mapping. Synthetic drumlins were, simplistically, considered to be 'found' if their centre points lay within a digitised outline; when multiple synthetics were encompassed the closest to the digitised outline's centre was selected. Subsequently, all mapped polygons (outlines, ridges, centre points) within shapefiles were re-numbered so their ID numbers matched those of the relevant synthetic drumlin. Thus, the behaviour of each drumlin's *H*, *W*, *L* triplet can be compared between interpreters, DEMs and visualisations.

3. Results

The five main synthetic DEMs were mapped by 25 interpreters giving a total of 21,625 drumlins to be identified by the group. 12,121 outlines were mapped in interpreters' preferred visualisations, 8,667 of which were coincident with the original synthetic drumlins. Table 1 presents an error matrix in the standard format used in remote sensing (e.g., Lillesand et al, 2008) reporting these results. For accessibility, the equivalent terminology from retrieval theory is also given (REF). The matrix shows that whilst the 'overall accuracy' is relatively low (8667/25,079) at 34%, the producer's accuracy, 'reliability' or 'precision' (8,667/12,121) is

relatively high at 72% (i.e., few false positives). This reflects the conservative number of drumlins generally mapped, but the high confidence in their accuracy. As a result, the user's accuracy, 'completeness', or 'recall' is also relatively low at 40% (8,667/21,625). Figure 2 shows the number of drumlins mapped by individual interpreters across all five DEMs; there is some variability in the totals mapped which is likely dependent upon the visualisation method and mapping philosophy employed by the individual. However, the number of correct drumlins is much more stable, typically between 300 and 500 landforms with a mean of 347 and standard deviation of 97.

To supplement the main mapping, 12 interpreters mapped one of four additional synthetic DEMs containing parallel alignment, a total of 2076 drumlins. The number of correctly mapped drumlins likely per five DEMs increases a little (t-test, unequal variance, $p=0.11$) for these DEMs to 402 with a standard deviation of 82 (Fig. 2), with the variability likely arising for similar reasons to that in maps 1-5. The increase in correctly mapped drumlins is driven by a moderately sized but notable increase in 'reliability' (885/1028) to 86%, leaving 'completeness' (885/2076) at the slightly raised level of 43% and 'overall accuracy' (885/2219) up to 40%, both still relatively low. So, mappers are able to make some use of parallel alignment although perhaps less than expected from the strength of feeling about this at the workshop. Idealised drumlin shapes combined with parallel alignment, especially when using a necessarily smoothed (2 km mean filter) flow field, arguably represents a best case scenario for detection.

Table 1: Error Matrix showing the number of correctly mapped drumlins in addition to errors of omission and commission. See text for an interpretation of the matrix. Figures for DEMs containing parallel alignment are given in brackets.

	Mapped	Not Mapped 'omission'	Total
Correct	8667 (885) [True positive]	12958 (1191) [False negative, Type II error]	21625 (2076)
Incorrect (commission)	3454 (143)		3454

	[False positive, Type I error]		(143)
	12121 (1028)	12958 (1191)	25079 (2219)

The maps present the outcomes of mapping from each of the individual interpreter's digitisation of drumlin outlines using their 'best' attempt based upon their preferred visualisation. Each of the five synthetic DEMs (Maps 1-5) is presented separately as part of an interactive PDF, as are the DEMs containing parallel conformity (Maps 6-9). The PDF is designed to be a digital product that the reader interacts with; map layers within the PDF can be turned on and off allowing the original synthetic drumlins to be viewed, along with mapping by each of the interpreters. This allows direct comparison by switching between layers. The underlying topography is displayed as relief shaded terrain illuminated from 315°. Additionally there are **two** layers that display the outlines of the synthetic drumlins: (1) the 'Number of Times Identified' layer shows the frequency with which the drumlin was correctly identified and (2) the 'Height' layer shows the elevation of the drumlin (classified using a Jenk's Natural Breaks algorithm).

4. Conclusions

Manual mapping of landforms from remotely sensed imagery remains a common task in the Earth sciences because it is both effective and practical to implement. In contrast, whilst automated and semi-automated detection methods have significantly improved, they remain difficult to implement and are of variable quality. Yet the objectiveness and repeatability of manual interpretation can be questioned. Testing the efficacy of mapping in an absolute sense is difficult as it is not possible to know, *a priori*, the landforms that actually exist in the landscape.

To this end, this work utilises innovative synthetic landscapes. The current process takes a DEM, removes existing landforms (specifically drumlins) and then uses the metrics from this landform population to parameterise a new idealised set that are inserted back in to the model DEM. Five variations of this landscape were generated and 24 interpreters with varying ability, experience, preferences, and time available mapped the drumlins within them. This provides a first assessment of mapper capabilities with respect to a known baseline. Each individual interpreter's mapped boundaries are overlaid on the DEMs and presented within the map accompanying this manuscript. As such the maps form a reference dataset. Initial results suggest that overall detection rates are relatively low, but reliability of mapping can be high.

Acknowledgements

The European Geophysical Union financially supported the workshop including the provision of travel grants to young researchers. Loughborough University and the CHES group in the Geography Department provided financial support and facilities for the workshop. Kathy Mather's quantitative MSc work, co-supervised by N. Woodcock, on drumlin morphology (Mather, 2008) acted as an early driver for this project. The NEXTMap DEM data were supplied to MS.

Software

Esri ArcGIS 10 was used for the production of the accompanying maps, with many of the individual mappers also using it to digitise the outlines of the synthetic drumlins. GMT (Wessel and Smith, 1998) was used for the underlying analysis; e.g., DEM production, outline renumbering.

Map Design

The accompanying atlas was designed from the outset as an interactive document that the reader can explore. It represents the output from the first ever attempt to objectively compare mapping of landforms by individual interpreters. An A1 page size was selected in order to maximise the resolution of the underlying raster topography, which is presented as a Swiss-type hillshade. **Each** map has a unique underlying DEM, varying according to where the synthetic drumlins are. Ancillary elements surround the map providing location, scale, title and legends. Palatino was selected for typography as a readable, "classic", style typeface.

The key part of the maps is the interactive layers; with the layer tab visible each layer within each page is visible. Any of these elements can have their visibility toggled on or off. There are three primary layers under "Main Map". "Mapping" shows all mapping of the individual interpreters; this whole layer, or individual sub-layers, can have their visibility toggled. "Times Identified" shows the actual synthetic drumlins and is symbolised based upon the number of times they were identified. "Drumlin Height (m)" is symbolised to show the height of the synthetic drumlins and is specifically included to emphasise the link with the number of times forms were identified.

References

Anders, N.S., Seijmonsbergen, A.C., Bouten, W., 2011. Segmentation optimization and stratified object-based analysis for semi-automated geomorphological mapping. *Remote Sensing of Environment* 115, 2976-2985.

Anonymous, 1963. Imagery interpretation section - the eyes of the division. US Army, 24th Infantry Division, Augsburg, Germany.

Armugam, R., Hillier, J. K., Smith, M., 2012. Quantifying how well drumlins can be mapped using synthetic DEMs. IAG/AIG International Workshop: 'Objective Geomorphological Representation Models: Breaking Through a New Geomorphological Mapping Frontier'. University of Salerno, Oct 15-19.

Behn, M. D., Sinton, J. M., Deitrick, R. S., 2004. Effect of the Galapagos hotspot on seamount volcanism along the Galapagos Spreading Center. *Earth and Planetary Science Letters*, 217, 331-347.

Boyce, J., and Eyles, N., 1991. Drumlins carved by deforming till streams below the Laurentide ice sheet. *Geology*, 19(8), 787-790.

- Braun, J., Sambridge, M., 1997. Modelling landscape evolution on geological time scales: a new method based on irregular spatial discretization. *Basin Research* 9, 27–52.
- Bue, B. D., and T. F. Stepinski, 2006. Automated classification of landforms on Mars, *Comput. Geosci.*, 32(5), 604–614, doi:10.1016/j.cageo.2005.09.004.
- Chase, C.G., 1992. Fluvial landscupting and the fractal dimension of topography. *Geomorphology* 5, 39–57.
- Chorley, R. J., 1959. The Shape of drumlins. *J. Glaciology*, 3, 339–344.
- Clark, C.D., Hughes, A.L.C., Greenwood, S.L., Spagnolo, M., Ng, F.S.L., 2009. Size and shape characteristics of drumlins, derived from a large sample, and associated scaling laws. *Quaternary Science Reviews* 28, 677-692.
- Colgan, P., Mickelson, D. M. (1997). Genesis of streamlined landforms and flow history of the Green Bay Lobe, Wisconsin, USA. *Sediment. Geol.*, 111, 7-25.
- Colwell, R.N. (Ed.), 1960. *Manual of Photographic Intrerpretation*. American Society of Photogrammetry.
- Drăguț, L., Blaschke, T., 2006. Automated classification of landform elements using object-based image analysis. *Geomorphology* 81, 330–344.
- Evans, I.S., 1972. General Geomorphometry, derivatives of altitude and descriptive statistics., In: Chorley, R.J. (Ed.), *Spatial Analysis in Geomorphology*. Harper and Row, New York, pp. 17-90.
- Evans, I. S., 2012. Geomorphometry and landform mapping: What is a landform? *Geomorphology*, 137, 94-106. doi:10.1016/j.geomorph.2010.09.029
- Finlayson, A., Merritt, J., Browne, M., Merritt, J., McMillan, A., Whitbred, K., 2010. Ice sheet advance, dynamics, and decay configurations: evidence from west central Scotland. *Quaternary Science Reviews*, 29 (7-8), 969-988.
- Fisher, P., Wood, J., Cheng, T., 2004. Where is Helvellyn? Fuzziness of multi-scale landscape morphometry. *Transactions of the Institute of British Geographers* 29, 106–128.
- Hillier, J. K., Watts, A. B., 2004. “Plate-like” subsidence of the East Pacific Rise - South Pacific Superswell system. *Journal of Geophysical Research*, 109(B10102).
- Hillier, J. K., 2008. Seamount detection and isolation with a modified wavelet transform. *Basin Research*, 20, 555-573.
- Hillier, J. K., Smith, M. 2008. Residual relief separation: digital elevation model enhancement for geomorphological mapping. *Earth Surface Processes and Landforms*, 33(14), 2266–2276. doi:10.1002/esp.
- Hillier, J.K., Smith, M.J., 2012. Testing 3D landform quantification methods with synthetic drumlins in a real digital elevation model *Geomorphology* 153-154, 61-73.

- Hillier, J.K., Smith, M.J., 2014. Testing techniques to quantify drumlin height and volume; synthetic DEMs as a diagnostic tool. *Earth Surface Processes and Landforms*, 39(5), 676-688, doi:10.1002/esp.3530.
- Hollingsworth, S. E. 1931. The glaciation of western Edenside and adjoining areas and the drumlins of Edenside and the Solway basin. *Quart. J. Geol. Soc. London*, 87(2), 281-359.
- Hughes, A.L.C., Clark, C.D., Jordan, C.J., 2010. Subglacial bedforms of the last British Ice Sheet. *Journal of Maps* 6, 543-563.
- Intermap, 2004. Intermap Product Handbook and Quickstart Guide (v3.3). Intermap, Englewood, California.
- Johnson, M. D., Schomacker, A., Benediktsson, I. O., Geiger, A. J., Ferguson, A., & Ingolfsson, O., 2010. Active drumlin field revealed at the margin of Mulajokull, Iceland: A surge-type glacier. *Geology*, 38(10), 943–946. doi:10.1130/G31371.1
- Kleman, J., Borgström, I., 1996. Reconstruction of palaeo-ice sheets: the use of geomorphological data. *Earth Surface Processes and Landforms* 21, 893-909.
- King, E. C., Hindmarsh, R. C. A., and Stokes, C. R., 2009. Formation of mega-scale glacial lineations observed beneath a west Antarctic ice stream. *Nat. Geosci.*, 2, 585–596.
- Lillesand, T.M., Kiefer, R.W., Chipman, J.W., 2008. Remote sensing and image interpretation. John Wiley and Sons, New York.
- MacLachlan, J. C., and Eyles, C., 2013. Quantitative geomorphological analysis of drumlins in the Peterborough drumlin field, Ontario, Canada. *Geografiska Annaler: Series A, Physical Geography*, 95(2), 125–144.
- Mather, K., 2008. Drumlins in the Howgills. MSc Dissertation. University of Cambridge.
- Menard, H. W., 1959. Geology of the Pacific sea floor. *Experientia*, 15, 205-244.
- Menzies, J., 1979. A review of the literature on the formation and location of drumlins. *Earth Science Reviews* 14, 315-359.
- Podwysoki, M.H., Moik, J.G., Shoup, W.C., 1975. Quantification of geologic lineaments by manual and machine processing techniques, Proceedings of the NASA Earth Resources Survey Symposium. NASA, Greenbelt, Maryland, pp. 885-905.
- Prest, V.K., Grant, D.R., Rampton, V.N., 1968. The Glacial Map of Canada, 1253A ed. Geological Survey of Canada.
- Punkari, M., 1980. The ice lobes of the Scandinavian ice sheet during the deglaciation of Finland. *Boreas* 9, 307-310.
- Reed, B., Galvin, C. J., and Millier, J. P., 1962. Some aspects of drumlin geometry. *American Journal of Science*, 260, 200–210.

- Rose, J., Letzer, J. M., 1975. Drumlin measurements: a test of the reliability of data derived from 1:25,000 scale topographic maps, *Geol. Mag.*, 112, 361–371.
- Rose, J., Letzer, J. M., 1977. Superimposed drumlins, *J. Glaciol.*, 18, 471–480.
- Rose, J., Smith, M.J., 2008. Glacial geomorphological maps of the Glasgow region, western central Scotland. *Journal of Maps* v2008, 399-416.
- Saha, K., Wells, N.A., Munro-Stasiuk, M., 2011. An object-oriented approach to automated landform mapping: A case study of drumlins. *Computers and Geosciences* 37, 1324-1336.
- Shaw, J., 1983. Drumlin formation related to inverted melt-water erosional marks. *J. Glaciology*, 29(103), 461–479.
- Shaw, J., Kvill, D., and Rains, B., 1989. Drumlins and catastrophic subglacial floods. *Sedimentary Geology*, 62(2), 177–202.
- Siegal, B.S., 1977. Significance of operator variation and the angle of illumination in lineament analysis of synoptic images. *Modern Geology* 6, 75-85.
- Sithole, G., and Vosselman, G., 2004. Experimental comparison of filter algorithms for bare-Earth extraction from airborne laser scanning point clouds. *ISPRS Journal of Photogrammetry & Remote Sensing*, 59, 85–101.
- Smalley, I., Lu, P., Jefferson, I., 2000. The Golf-Ball Model and the Purpose of Drumlin Formation. *Studia Quaternaria*, 17, 29-33.
- Smith, A.M., Murray, T., Nicholls, K.W., Makinson, K., Adalgerisdottir, G., Behar, A.E., Vaughan, D.G., 2007. Rapid erosion, drumlin formation, and changing hydrology beneath an Antarctic Ice Stream. *Geology*, 35, 2, 127-130.
- Smith, M.J., Clark, C.D., 2005. Methods for the visualisation of digital elevation models for landform mapping. *Earth Surface Processes and Landforms* 30, 885-900.
- Smith, M.J., Rose, J., Booth, S., 2006. Geomorphological mapping of glacial landforms from remotely sensed data: an evaluation of the principal data sources and an assessment of their quality, *Geomorphology*, 76, 148–165.
- Spagnolo, M., Clark, C. D., & Hughes, A. L. C., 2012. Drumlin relief. *Geomorphology*, 153-154, 179–191.
- Stokes, C. R., Clark, C. D., 2002. Are long subglacial bedforms indicative of fast ice flow? *Boreas*, 31(3), 239–249.
- Thompson, M.M., 1966. *Manual of Photogrammetry*, 3rd ed. ASPRS, Virginia Falls.
- Van Asselen, S., and A. C. Seijmonsbergen, 2006. Expert-driven semi-automated geomorphological mapping for a mountainous area using a laser DTM, *Geomorphology*, 78(3-4), 309–320, doi:10.1016/j.geomorph.2006.01.037.

Wellner, J.S., Lowe, A.L., Shipp, S.S., Anderson, J.B., 2001. Distribution of glacial geomorphic features on the Antarctic continental shelf and correlation with substrate: implications for ice behavior. *Journal of Glaciology*, 47, 158, 397-411.

Wessel, P., Smith, W.H.F, 1998. New, improved version of Generic Mapping Tools released, *EOS Trans. Amer. Geophys. U.*, 79 (47), 579.

Figures




Fig 1: a) Location of the study area. b) Drumlins (black) in the area as mapped by Smith et al (2006). c) Recovery (i.e., 'completeness') as a function of size; synthesis of a manual mapping pilot study (Armugam et al, 2012). Methodology was as here (see 'Interpretive Mapping'), but applied to 10 DEMs equivalent to Maps 1-5 using only one mapper. Black line is for height, H , and grey lines are for width W (solid) and length L (dashed). Circles are means with their standard errors for the 10 DEMs, and dashed line is for medians. H , W , and L have bin widths of 2.5, 25, and 100 m, respectively. At the upper end, bins with two or fewer input data are omitted, giving maxima of 20, 275 and 800 m, respectively. All data are plotted centrally within bins.




Fig. 2: Number of drumlins mapped per individual interpreter (black) and the number correct (red). Blue triangles are for the number correctly mapped in synthetic DEMs with parallel conformity, scaled ($\times 5$) to allow comparison. Horizontal black line is the number of drumlins in the synthetics. This was known to the mappers.